CLEANING MANUAL

Welcome and congratulations on your purchase of the renowned VisibleDust sensor cleaning technology. This manual is our comprehensive guide to assit you in both wet and dry cleaning techniques. We've prepared a simple, step-by-step process and Frequently Asked Questions section for your convience. You'll also find topics on cleaning theory, how your camera becomes dirty, cleaning with alcohol and other important topics. We want you to be prepared for every challenge, and with the information outlined within this guide, you too will be capable of identifying and treating various contaminations.



Two particles hugging the fibers of the Sensor Brush™ filaments.

Products this guide covers:

- Arctic Butterfly® 724
- Arctic Butterfly® SL700
- Arctic Butterfly® SD800
- Sensor Brush™
- Sensor Loupe™
- VisibleDusts Swabs
- Sensor Clean™
- VDust™ Plus
- Smear Away™

WHY CLEAN MY SENSOR?

Dust in images just comes included in the package when you became a photographer. They're the variable in the equation that turns a photoshoot into work. A clean sensor can make the difference between a photo, and a great photo!

Cleaning a dirty sensor, is considered taboo for many photographers. Although new cameras are now coming equipped with anti-dust technology to help ease the pain; like a computer virus, dust still manages to slip by, ruining your images. With VisibleDusts cleaning system, you can enjoy the comfort of knowing your sensor is truly clean with manufacturer quality. In our efforts to address the issue of dust, VisibleDust has developed leading, cutting edge technologies that not only clean and protect your sensor, but prolong your camera cleaning.

VisibleDust is prepared to both educate and guide you as you grow from this new experience. For some, VisibleDusts products' have a spot right beside your camera lens; others are seeking to find the **simple**, **safe solution** that everyone's been talking about. Whatever your reasons are for turning to VisibleDust, you won't need to look anywhere else.

HISTORY OF SENSOR BRUSH™

Sensor Brush™ and Arctic Butterfly® 724

VISIBLEDUST was first founded in the fall of 2004 by Dr. F Dehghan. Finding dust a everyday problem, Dr. Dehghan's used his expertise and knowledge of biochip technology to develop the world's first Sensor Brush™. Attracting protein and DNA to the glass-like surface of a biochip for attachment requires special preparation of that surface. Because dust has many common characteristics with DNA, VisibleDusts DSLR sensor cleaning products are able to utilize the same technology. Sensor Brush™ was an instant win with photographers everywhere and propelled VisibleDust into the industry leader. VisibleDusts flagship product Sensor Brush™, has since evolved into the renown Arctic Butterfly® models. Although Sensor Brush™ has gone through many stages to become what it is today, the core components of being **safe**, **effective**, and **economic** are still the heart and soul.

The company has since become the major player in the industry for sensor cleaning. Our scientific drive has introduced leading products such as VDust™ Plus, Smear Away™ and our patent pending swab line-up. Our system is considered to be the safest, most economical and most efficient choice on the market for cleaning your sensor. We are proud to put our biochip knowledge to the test by bringing you scientifically proven products. VisibleDust always gives you our best, from our labs to your camera bag.

CLEANING THEORY

WET & DRY cleaning techniques exist in various products throughout the industry. Ranging from traditional alcohol to VisibleDusts Sensor Brush™. VisibleDusts research and development have resulted in the industries only **scientifically proven** wet and dry cleaning products. The focus of this manual will be to provide you with the technique and knowledge required to clean using both methods. A full detail for cleaning your camera falls into three steps: Inspection, Dry Cleaning and Wet Cleaning.

INSPECTION involves checking over the camera to identify what methods will be used and which areas need to be cleaned. VisibleDusts **Sensor Loupe™** is a small, portable tool for a quick assessment for various components of the camera.

DRY cleaning is generally the most common method used. Dry cleaning involves no liquids or swabs from VisibleDust. Only VisibleDusts Sensor Brush™ or Arctic Butterfly® products should be used for dry cleaning. The filaments of both our Sensor Brush™ and Arctic Butterfly® are equipped with SCF technology, enabling them to safely and effectively clean your sensor.

Contaminations that both the Arctic Butterfly® or Sensor Brush™ will remove include loose and free particles. As seen in the image, the surface of a sensor is home to deep pits and grooves. Since dust can easily attach itself into these crevasses, a physical force is required to "kick" the dust free. Once free, the particles are attracted to the filaments of the Arctic Butterfly® or Sensor Brush™. The objective of dry cleaning is either, (a) to remove physical particles from the sensor surface, or (b) to remove all potential scratching hazards; preventing them from collecting along a swab edge. Your sensor would now be prepped and ready for a wet cleaning.

Micro-grooves and channels from a sensor scratch.

WET cleaning is for stains, smears and stubborn dust. Without magnification, distinguishing the difference between a stain and speck of dust is difficult. Always dry clean before you wet clean. You wouldn't want any loose particles to get dragged from one end to the other; potentially a scratching hazard.

Stains or smear on the surface of a sensor can be composed with a variety of elements. Air pollution such as smoke, diesel fumes, or pollen can combine with the present dust on the sensor resulting in a stain. Oils and lubricants from within the camera can mix and then stick to the surface. There are many factors that all contribute to how stains and smears are formed, from humidity to air temperature. The composure of a stain will vary from water-based to oil-based. VisibleDust has three wet cleaning solutions that target specific types of contaminants within that range.

Typically dust will have the appearance of a small spec. Spots or specs that do not move (by either the physical force of the filaments or a swab edge) may be a scratch. If you're using the f/22 test to spot contaminants; make sure your lens is clean. Not all contaminants appearing in the image may be on the sensor itself.

PRECLEANING

INSPECTING for contaminants on your sensor is recommended in two methods and should always be done pior to cleaning. VisibleDusts Sensor Loupe™ is highly recommended for photographers in the field, or for cleaning centres, the f/22 test.

Sensor Loupe™ utilizing BriteVue™ XL Technology

SENSOR LOUPE™ is a stand-alone optical inspection device that magnifies the sensor surface for viewing. It's compact, mount free design also allows it to be used for inspecting the chamber, focusing screen, mirror and lens for contaminants. Sensor Loupe™ offers the brightest, most compact and biggest magnification on the market. This solution is perfect to see what you're up against.

Sensor Loupe™ is designed to be very easy to use. Simply activate the BriteVue™ lights and inspect either your sensor, chamber, focusing screen or mirror. Every photographer has their own personal preference to position and distance; you'll find right away which style best suits you.

THE f/22 TEST is recommended for cleaning centres, as it allows for **before and after** comparison shots. Set your digital SLR cameras f-stop to 22, and disable automatic focusing. To avoid vignetting, use a 35mm or higher lens. Do not use a wide angle lens. Take a picture of a singular, uniform-lite backdrop. A cloudless sky or white wall work best. Examine the images by zooming in on them with your cameras LCD preview screen. Should you have access to a personal computer with a valid copy of Adobe® Photoshop®, you can load your image and apply the Autolevels adjustment (Image>Adjustments>Autolevels).

For cleaning centres and demos, VisibleDust highly recommends the f/22 method for liability purposes. Saving a **before cleaning** and **after cleaning** shot is perfect for comparisons.

Dust settled on the singlet can show in the f/22 test.

PRECLEANING should begin with a thorough inspection of the camera, along with taking the f/22 test. Checking over all the components before you clean will yield an abundance of information, giving you a clearer picture of what materials and methods you'll need to apply. Be sure to check over the external body, viewfinder, chamber, mirror, focusing screen, lens mount, LCD screen, singlet and outer lens. Identify which areas will require a wet or dry cleaning. After a quick assessment you're ready to take the f/22 test. Before **any** cleaning is done, take a before shot using the f/22 test. Be sure your lens is clean beforehand. Dust and oil on your lens can show up in the test results, tainting the outcome.

DRY DUST is 90% of the time the culprit. When inspecting with **Sensor Loupe™**, check all four corners, edges and remote locations for dust. When inspecting your f/22 test results, dust will have the appearance of small black specs. Spots typically have halos around them, and sometimes take the appearance of dry dust. Scratches will appear as an immobile line and are noticeable immediately. Loose particles will be removed during a dry cleaning. Remaining spots/stains are classified as stubborn dust and require a wet cleaning for removal.

A mirror in desperate need of a wet and dry cleaning.

DRY CLEANING

STEP 1 - REMOVE CAP & SPIN

Remove the protective cap of the Arctic Butterfly® model by twisting the cap and pulling it off. Turn the Arctic Butterfly® on and allow it to spin for 5–10 seconds. The bristles should fan out to a flat 180°.

1a



1b

STEP 2 - CLEAN SENSOR SURFACE

Method A

Refer to your camera's user manual to properly expose the sensor chip. Take caution not to touch the chamber walls while cleaning, entering and exiting. Gently clean across the sensor surface with one uniform pass, allowing dry dust particles to be statically attracted to the bristles.

2.1a



2.1b



Method B

Small specks and spots of dry dust require only a light dabbing procedure. Instead of cleaning end-to-end, lightly tap the bristles on dust specks to remove them.

2.2a



2.2b



STEP 3 - CHARGE & DISLODGE

Charge the bristles and dislodge any dry dust particles from the Arctic Butterfly® by turning it on OUTSIDE of the camera. Check your sensor for dust particles with Sensor Loupe™ (sold separately) and repeat steps 1–3 if needed.

Spin the Arctic Butterfly® (Charge & Dislodge) outside and away from the camera after EACH brush stroke.

DRY CLEANING BEST PRACTICES

The Arctic Butterfly® is a tool for safely removing dust particles from the sensor's surface. Some cameras contain oily chambers or sensor chip perimeters; avoid contact with your chamber while cleaning your sensor. Contaminants on the brush head will affect performance. For stains, smears, smudges, camera oils and lubricants, look to VisibleDust's travel safe wet cleaning solutions.

DO NOT:

- activate the Arctic Butterfly® while cleaning (Figure 8.1).
- apply excessive pressure while cleaning (Figure 8.2).
- contaminate the bristles with oils or liquids.
- clean with a contaminated brush head.
- activate the Arctic Butterfly® while the protective cap is still attached.

ALWAYS:

- stow the Arctic Butterfly® in its case with the cap on when not in use.
- remove the batteries when traveling on an airplane.
- clean your brush head every 10–15 uses or as needed.
- activate the Arctic Butterfly® inbetween cleaning strokes, outside the camera.

8.1



8.2



ARCTIC BUTTERFLY® MAINTENACE

Cleaning

You should clean your Arctic Butterfly® brush head and cap every 10–15 uses or as soon as contamination occurs. Should your brush head bristles fray or bend out of shape, you may dip the brush head in warm water (50°C or 122°F) for 10 seconds to straighten the bristles. Do not use hot or boiling water to clean the brush head, as this will permanently damage the bristles.

Contamination from oils or liquids will hinder the performance of the Arctic Butterfly®. Should your brush head become contaminated, VisibleDust's Sensor Brush Wash™ (sold separately) can clean the fibers of any impurities. In the absence of Sensor Brush Wash™, pure isopropyl alcohol (99%) is also an acceptable solvent. Do not use methanol!

Switching Brush Heads

Only the Arctic Butterfly® models 724 and SD800 Pro have detachable brush heads that are interchangeable. To remove those brush heads, pull them off at the white adapter base. You can then attach either the HDF brush head or the SD800 Pro adapter to mount the 1.6x, 1.3x, 1.0x or the new Angle 45 brush. To prevent loud vibrations, wobbling or reduced spin speed, be sure to firmly attach the adapter/brush head.

A



Pull at the white base

B



Firmly attach brush head

WET CLEANING

STEP 1 - APPLY SOLUTION TO SWAB

Remove a swab from its clean room bag carefully. Apply cleaning solution to the appropriate swab until semi-wet. Should your swab dry out, add more solution. Amount of solution varies for swab sizes. Please review the Wet Cleaning Guide (page *) if you are unclear which liquids and swabs are compatible.

Try not to let the swab touch the adhesive while removing it from the clean bag.

Should your swab dry out then apply more solution.

It is not uncommon for a swab to occasionally rub contaminants off the chamber sides while cleaning. Should any new dust spots become visible, use an Arctic Butterfly® for dust removal.

STEP 2 - CLEAN SENSOR SURFACE

Refer to your cameras user manual to properly expose the sensor chip. Take caution not to touch the chamber walls while entering/exiting. Gentlely clean across the sensor surface with one uniform pass.

A



B



Both sides of the swab may be used to clean. Use each side of the swab only once during cleaning. Cleaning with a contaminated swab edge can potentially harm the sensor. You may be required to add additional cleaning solution to the opposite side. It is not uncommon for a swab to occasionally rub contaminants off the chamber sides while cleaning. Should any new dust spots become visible, use an Arctic Butterfly® for dust removal.

STEP 3 - DISCARD SWAB & INSPECT

Swabs should be discarded after use. Check your sensor for smears or stains with Sensor Loupe™ and repeat steps 1–3 if needed. For a complete cleaning, follow up with an Arctic Butterfly® to remove any dry contaminants that may be present.

SPECIALITY SWABS

VisibleDust is committed to providing the right tools for any situation. Our speciality swabs are designed for case senarios where our regular swab aren't suitable. Simply apply the proper amount of solution and clean the designated area.

Corner Swabs A

Apply one drop of solution

Corner Swabs B

Gently clean your corners, edges or rub a remote contamination.

Focusing Screen Swabs A

Apply 1-2 drops of Sensor Clean™

Focusing Screen Swabs B



Gently clean the focusing screen in one uniform pass.

To avoid damage to your focusing screen, clean only with Sensor Clean™. Do not use any alcohol/methanol based products to clean your focusing screen.

WET CLEANING BEST PRACTICES

VisibleDusts Wet Cleaning solutions are each tailored to remove different traces of contaminations. VisibleDust strongly recommends you dry clean with an Arctic Butterfly® or Sensor Brush™ first to safely remove hard, dry dust particles. See Cleaning Theory for more details.

DO NOT:

- clean with a contaminated swab
- apply solutions to incompatible swabs
- apply an excessive amount of solution to the swab
- recycle a swab once you've finished cleaning with it
- allow a swab to dry out.
- apply an excessive amount of pressure when cleaning

ALWAYS:

- use the appropriate swab with its matching solution
- stow solutions with their cap on when not in use
- use the proper sensor size specific swab to clean

STREAKS & SMEARS

When wet cleaning it's important to use the appropriate swab or streaks/residue may be left behind. Generally, the contaminations on your sensor range from water to oil based. The chart below helps you visualize each products capabilities for removing contaminates.



Smear Away™
Anti-Static Coating ★★★★★
Good for removing strong contamination buildup. Designed to remove heavy oils, stains, lubricants and smears.

VDust™ Plus
Anti-Static Coating ★★½☆☆
A good mid-range product if you're not sure what's on your sensor. Start out with VDust™ Plus and see whether you need a stronger or lighter remover.

Sensor Clean™
Anti-Static Coating ★★★★★
A light removal solution. Excellent for water-based contaminations such as condensation, saliva, or streaks.

Orange DHAP Series Swabs Compatible
Green Ultra MXD-100 Swabs Compatible

CLEANING WITH ALCOHOL

VisibleDust recognizes that the current market is flooded with alcohol cleaning solutions. To cater to this market, we've developed our Orange DHAP swabs. Simply follow our 3-step instructions, using an isopropyl/alcohol product of your choice.

Alcohol cleans through rapid dehydration and evaporation. However, the extremely dry surface is prone to scratching easier and attracting dust. Alcohol also lacks the ability to dissolve protien based contaminations. Methanol and alcohol based solutions are restricted for airplane travel.

Generally water-based solutions are recommended for anti-static and anti-fogging coatings. Alcohol-based is for oil removal.

FREQUENTLY ASKED QUESTIONS - DRY

Q: How safe is the Arctic Butterfly® on my sensor?
A: Very safe. The brush head fibers are soft enough not to scratch and will not dissipate their positive charge onto the sensor. When used incorrectly or for purposes other than the original intent, damage may occur.

Q: How does the Arctic Butterfly® clean my sensor?
A: The permanently charged fibers attract dry dust particles that come near them.

Q: How do an Arctic Butterfly® and Nylon brush differ?
A: VisibleDust incorporates SCF (Super-Charged Fiber) technology to attract dry dust. Our bristles undergo a patent pending procedure to become ionized and permanently charged. Nylon brushes are not suitable for removing dust and therefore not recommended. Only VisibleDusts patented Sensor Brush™ technology is qualified to remove dry dust through enhanced SCF electric attraction.

Q: Is the Arctic Butterfly® all I need to clean my sensor?
A: 95% of the time will require an Arctic Butterfly® for removing dry dust. Minor stains, smears and oils require a wet cleaning to be removed. Look to VisibleDusts travel safe, wet cleaning solutions for stubborn dust, stains, smears and oils.

Q: How do I clean my brush head if it becomes contaminated?
A: Please review the Maintenance section of this manual for more information.

Q: How many cleanings is the Arctic Butterfly® good for?
A: The Arctic Butterfly® is good for up to 10,000 cleanings and based on the average cost, that's less than 1¢ per cleaning.

Q: Should the Arctic Butterfly® vibrate or buzz while activated?
A: Small vibrations are acceptable; however, if you're experiencing loud buzzing or if the brush head is wobbling, the cause may be a loose brush head rubbing against the casing. Attach the brush head firmly enough for the wobbling or vibrations to stop.

FREQUENTLY ASKED QUESTIONS - WET

Q: How safe are VisibleDusts liquid solutions on my sensor?
A: Very safe. Our solutions should only be used AFTER you've dry cleaned your sensor with an Arctic Butterfly®.

Q: How travel friendly are your liquid solutions?
A: Unlike alcohol and methanol based solutions, VisibleDusts products are safe. This makes them ideal for travelling on an [1]airplane.

Q: How do the Green and Orange swabs differ?
A: The difference between our DXM-100 (Green) and DHAP (Orange) swabs is the type of fabric used in assembly. The Green swabs are compatible with all of our sensor cleaning solutions, so when in doubt purchase the green. If you prefer to clean with isopropyl alcohol, then purchase the Orange swabs. Orange swabs also work best with VDust™ Plus.

Q: Do your water-based solutions evaporate fast?
A: Yes! When used in conjunction with the appropriate swabs, you won't need to wait long.

Q: Can I use your solutions to clean other surfaces?
A: Yes; however, each of our products are tailored for different senarios and VisibleDust recommends using each product for its original intent.

Q: Can I use just Smear Away™ for all my wet cleaning?
A: No. Smear Away™ is designed with powerful cleaning agents and should be used for severe stains or smear.

Q: Do your liquids leave any streaks?
A: If too much liquid, or the inappropriate swab is used, then streaks may occur.

[1]Some airports may restrict carry-on liquids

CONTACT

This manual is a work in progress and none of the information presented here represents the final version. For more information contact VisibleDust.

matt@visibledust.com
780.455.1082
www.visibledust.com